

HOT STRIP MILL  
SALDANHA STEEL  
SPINDLE CONDITIONS

Spindle	Adaptor FLATS	RE adaptor	RE hub	PE hub	Ring Gear	RE Stub	PE Stub	Date listed
	355.3H9	Ø 613.05	Ø 663.55	Ø 663.55	Ø 613.33	Ø 514.00	Ø 514.00	
FM1/2-1	355.4mm	610.3mm	NEW	665.3mm	N/A	NEW [welded]	515.9mm	13-Dec-13
FM1/2-2	355.4mm	610.5mm	664.5mm	664.4mm	N/A	515.2mm	516.0mm	29-Jul-14
FM1/2-3	355.7mm	610.7mm	665.9mm	665.5mm	N/A	515.9mm	516.2mm	06-May-14
FM1/2-4	355.4mm	610.0mm	644.0mm	644.2mm	N/A	516.0mm	515.0mm	30-Jan-14
FM1/2-5	335.3mm	610.8mm	665.2mm	664.9mm	N/A	515.7mm	515.4mm	30-Sep-13
FM1/2-6	356.0mm	610.8mm	665.6mm	665.5mm	N/A	516.5mm	516.7mm	28-Mar-14
FM1/2-7	356.2mm	611.3mm	664.2mm	665.7mm	N/A	516.1mm	516.9mm	30-Sep-14
FM1/2-8	357.0mm	611.4mm	666.1mm	665.5mm	N/A	515.2mm	516.7mm	19-Mar-14
	355.3H9	Splines	Ø 536.47	Ø 536.47	Ø 488.65	Ø 373.00	Ø 373.00	
FM3-1	355.5mm	GOOD	537.9mm	537.9mm	486.3mm	375.2mm	374.5mm	22-Aug-14
FM3-2	355.2mm	GOOD	NEW	537.0mm	484.7mm	374.6mm	374.7mm	20-Jun-13
FM3-3	357.0mm	GOOD	537.3mm	538.1mm	486.3mm	374.0mm	374.6mm	20-Jun-13
FM3-4	355.5mm	GOOD	537.7mm	537.7mm	486.5mm	374.7mm	374.8mm	22-Aug-14
	268.3H9	Splines	Ø 442.67	Ø 442.67	Ø 407.34	Ø 315.00	Ø 315.00	
FM4/5-1	269.3mm	GOOD	443.9mm	443.0mm	405.5mm	316.19mm	316.19mm	21-May-13
FM4/5-2	269.5mm	GOOD	443.2mm	443.8mm	406.5mm	317.1mm	316.7mm	22-May-14
FM4/5-3	269.6mm	GOOD	443.1mm	443.5mm	406.7mm	315.9mm	316.1mm	11-Feb-14
FM4/5-4	NEW	NEW	443.5mm	443.2mm	406.0mm	316.2mm	315.9mm	30-Jun-12
FM4/5-5	268.5mm	GOOD	442.8mm	443.4mm	406.4mm	315.1mm	316.6mm	30-Apr-14
FM4/5-6	269.4mm	GOOD	443.5mm	443.4mm	406.4mm	316.6mm	316.9mm	09-Jul-14
FM4/5-7	268.3mm	GOOD	NEW	443.7mm	406.5mm	316.7mm	316.5mm	26-Sep-14
FM4/5-8	268.7mm	GOOD	443.6mm	443.6mm	405.6mm	316.8mm	316.5mm	29-May-14
	365H9	Splines	Ø 663.55	Ø 663.55	Ø 613.33	Ø 514.00	Ø 514.00	
RM1	366.9mm	GOOD	665.6mm	665.4mm	611.2mm	515.6mm	516.6mm	25-Mar-14
RM2	365.4mm	GOOD	665.8mm	665.2mm	610.8mm	516.4mm	515.4mm	22-Apr-14
RM3	NEW	NEW	665.0mm	665.0mm	NEW	515.6mm	515.0mm	10-Sep-13
RM4	365.6mm	693.5mm	664.0mm	664.7mm	611.1mm	516.3mm	516.3mm	19-Nov-13
RM5	365.4mm	692.7mm	NEW	NEW	610.4mm	516.4mm	516.4mm	20-Nov-13
RM6	365.4mm	GOOD	665.0mm	665.0mm	610.2mm	515.5mm	516.3mm	09-May-13